



# MAYOR EPOXY FLOOR

## paintable epoxy floor

**Description** Mayor epoxy floor is floor coating based on epoxy resin, it can be colored

- Advantages**
- Give a smooth surface easy to clean
  - Give exceptional clarity
  - High UV resistant
  - High coverage
  - It can be colored with epoxy-based Mayor colors

- USES**
- Designed for smaller maintenance and repair jobs
  - Ideal for application which required high heat resistance
  - used in internal application

**Product Date**

**Component A** : white Liquid  
**Component B** : semi transparent Liquid  
**Pot Life** : 30 months  
**Touch Dry** : 8 - 10 hours  
**Hard Dry** : 24 months  
**Full hardness** : 7 days  
**Packaging** : (A+B) kg  
**Shelf Life**: 24 months from production date if stored according to storage conditions

- Storage conditions**
- It should be stored in good ventilated area protected from heat and direct sunlight
  - The container must be tightly closed

**Application Details**

Substrate Preparation:-  
Ensure that concrete floor is 28 days old and the surface moisture content less than 5% prior to the application  
Clean the surface from all dust, dirt, degradable type curing compound, oil and grease, cement laitance and other contaminants which will affect the bonding



### **Product Preparation**

- Mix all Liquid component A & B using electric mixer
- Apply product and leveled with rubber mop or roller paint
- Remove air with Mayor epoxy floor by spike roller
- Close the site for 24 hours until hard drying

### **Safety precaution**

It is preferable to apply product in good ventilated area  
suitable protective clothing, gloves, goggles and mask are recommended during application  
stain on the skin shall be washed splashed into eyes, wash immediately with plenty  
of water

Don't dispose of into water or soil, but according to local regulations.